

monosplit classe A

-  Moisture
-  Up/Down
-  Auto flaps
-  Auto Shut flaps
-  Adjust
-  Restart
-  Auto Changeover
-  Sleep
-  Program

FG 09USB A+A
 C 2,90kw - 9900btu
 H 3,05kw - 10400btu



FG 12USB A+A
 C 3,70kw - 12600btu
 H 4,00kw - 13600btu



FG 14USB B+A
 C 4,25kw - 14500btu
 H 4,80kw - 16400btu



- Bassi consumi
- Aria più pulita
- Alta silenziosità
- Riavvio automatico
- Deumidificazione equilibrata
- Acceso spento programmabile

FG 18UBA A+A Double
 C 5,40kw - 18400btu
 H 5,70kw - 19500btu



TIMER
GIORNALIERO

MODELLO		FG09USB	FG12USB	FG14USB	FG18UBA
Classe energetica		A / A	A / A	B / A	A / A
EER	kw/kw	3,45	3,27	3,08	3,25
COP		4,07	3,85	3,78	3,61
Capacità / Rese	Raffr. kw	2,90	3,70	4,25	5,40
	Risc. kw	3,05	4,00	4,80	5,70
	Raffr. Btu/h	9900	12600	14500	18400
	Risc. Btu/h	10400	13600	16400	19500
C.ità di deumidificazione	l/h	1,3	1,9	2,0	2,0
Volume aria trattata U.I.	m³/h	C 600 - H 600	C 700 - H 675	C 700 - H 675	C 950 - H 960
Volume aria U.E.	m³/h	1570	1710	1670	3200
Rumorosità U.I.	db(A)	C27 - H 26	C29 - H28	C37 - H 32	C 32 - H31
Rumorosità U.E.	db(A)	45	48	47	48
GAS		R410A	R410A	R410A	R410A
	Alimentazione	V/Ph/ Hz	230 / 1 / 50	230 / 1 / 50	230 / 1 / 50
Corrente assorbita	Raffr. (A)	3,7	5,0	6,1	7,3
	Riscald. (A)	3,3	4,6	5,6	7,0
Potenza assorbita	Raffr. (kw)	0,84	1,13	1,38	1,66
	Riscald. (kw)	0,75	1,04	1,27	1,58
Dimensioni U.Interna	(mm)		275 x 790 x 215		320x1120x220
Dimensioni U.Esterna	(mm)		535 x 695 x 290		650x830x320
Tubazioni frigorifere	Gas/Liquido	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	1/4 - 5/8
Max. l.za linea (dislivello)	mt	15 (8)	15 (8)	15 (8)	20 (8)
Preacarica	mt (gr) / ag.ta	7,5 (900) / 20	7,5 (970) / 20	7,5 (1040) / 20	7,5 (1550) / 20
Unità alimentata (nr.cavi di colleg.to)		Interna (4+T)	Interna (4+T)	Interna (4+T)	Esterna (4+T)
Temp. Di funzionamento	Raffresc. °C	21 ± 43	21 ± 43	21 ± 43	- 5 ± 43
	Riscald. °C	- 5 ± 24	- 5 ± 24	- 5 ± 24	- 10 ± 24
Comando	IN infrarosso	IN	IN	IN	IN